CLAIMS

What is claimed is:

A tool comprising:

an elongate body portion;

a handle portion attached at one end of the body portion;

an applicator portion attached to the other end of said body

portion, said applicator portion being sized and shaped for insertion under soil and forming an opening in said soil by lateral movement of said handle portion, said applicator portion defining at least one fluid outlet;

a fluid inlet, said fluid inlet being in fluid communication with said applicator portion, such that fluid applied under pressure to said inlet is dispense from said fluid outlet.

15

10

- 2. The tool of Claim 1 further comprising a valve interposed between said fluid inlet and said fluid outlet for selectively dispensing fluid from said fluid outlet.
- 20 3. The too of Claim 1, wherein said fluid inlet is connected to said tool adjacent said handle portion.
 - 4. The tool of Claim 1, wherein said valve is connected to said tool adjacent said handle portion.

25

- 5. The tool of Claim 1, wherein said body portion is hollow so that fluid can flow therethrough.
- 6. The tool of Claim 1, wherein said applicator tip is at least partially hollow so that fluid can flow therethrough.
 - 7. The tool of Claim 1, wherein said applicator tip is wedge-shaped.

The tool of Claim 1, wherein said applicator tip defines a plurality of fluid hozzles disposed in a fan-shape.

9. 5 The tool of Claim 1, wherein said applicator tip defines a plurality of fluid nozzles that dispense said fluid in a stream.

10. The tool of Claim 1, wherein said applicator tip houses a plurality of fluid dispensing prongs.

10

15

20

11.

A method of applying a pesticide comprising the steps of: inserting at least a portion of an elongate tool below the surface of soil, said tool comprising an applicator tip, a handle portion and an intermediate body portion, said applicator tip being in fluid communication with a fluid inlet port, said applicator tip defining at least one fluid outlet and a valve disposed between said inlet port and said applicator tip for selectively delivering

fluid pesticide to said fluid outlet, said applicator tip being sized and shaped for below grade insertion and for opening a furrow in said soil;

moving said handle portion of said tool laterally so that said applicator tip opens a furrow in said soil; and

actuating said valve to dispense liquid pesticide from said fluid outlet into said open furrow.

- 12. The method of Claim 11, wherein said fluid inlet is connected to said tool adjacent said handle portion. 25
 - The method of Claim 11, wherein said body portion is 14. hollow so that fluid can flow therethrough.
- 15. The method of Claim 11, wherein said applicator tip is at 30 least partially hollow so that fluid can flow therethrough.

16. The method of Claim 11, wherein said applicator tip is
wedge-shaped.
\
17. The method of Claim 11, wherein said applicator tip
defines an elongate slot through which fluid is dispensed.
18. A method for the subterranean application of a pesticide
comprising the steps of:
inserting a portion of an elongate, fluid conducting tool
below the surface of soil;
laterally moving the portion of said tool not below the
surface of said soil, such that said tool opens a furrow in said soil; and
providing liquid pesticide under pressure to said tool so that
said liquid pesticide is dispensed from said portion of said tool below said surface
of said soil into said furrow.
19. The method of Claim 18, wherein said liquid pesticide is
selectively dispensed from said portion of said tool into said furrow.
20. The method of Claim 19, wherein said liquid pesticide is
selectively dispensed from said tool by manual operation of a valve.
dispensed from said to a cy manual operation of a vario.
21. The method of Claim 20, wherein said valve is attached to
said portion of said tool above said surface of said soil.
22. The method of Claim 18, wherein said tool further

comprises a handle portion attached to said portion of said tool above said surface

of said soil.

23.	A method protecting a structure against attack from	
subterranean termites comprising the steps of:		
	(a) inserting a portion of an elongate, fluid conducting tool	
below the surface of soil;		
	(b) laterally moving the portion of said tool not below the	
surface of said soil,	such that said tool opens a furrow in said soil;	
	(c) providing liquid pesticide under pressure to said tool so	
that said liquid pest	icide is dispensed from said portion of said tool below said	
surface of said soil in	1 1	
	1 1	

(d) repeating steps a through c at intervals until a periphery of soil is treated surrounding said structure.

24. The method of Claim 23, wherein said interval is approximately every foot.

15

10

5